## **MATERIAL (SAFETY DATA SHEET)**



#### PRODUCT PREMIUM PIT RESIN

Product code: 30290, 30291, 30294, 30298, 30299, 30355, 30770, 30870, 30885

Synonyms: Polyurethane Oligomer Mixture

Manufacturer/Supplier Chemtel

Delta Kits Inc. 1090 Bailey Hill Rd. Suite A Emergency Telephone number (800)-255-3925 US Eugene Or. 97402 (813)-248-0585 Int.

Tel: 800-548-8332 Fax: (541)345-1591

#### Hazard identification

Hazard description: Irritant Appearance: Transparent Physical state: I Liquid

Classification: OSHA Regulatory Status: This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation Category 2 Serious eve damage/eve irritation Category 1 Skin sensitization Category 1 Specific target organ toxicity (single exposure)
Target Organ Effects: Category 3

Skin, EYES, inhalation, inge



Signal word

DANGER

#### GHS label elements, including precautionary statements

Hazard statements: Causes skin irritation and serious eye damage. May cause an allergic skin reaction and respiratory irritation. May be harmful if swallowed.

Precautionary Statements - Prevention: Wash face, hands and any exposed skin thoroughly after handling, Wear protective gloves/clothing/eye and face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well ventilated area.

Precautionary Statements - Response: Get medical advice attention if you feel unwell.

IF IN EYES; Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation or rash occurs: Get medical advice/attention.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

IF SWALLOWED: Rinse mouth.

Precautionary statements - Storage: Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal: Dispose of contents/container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC): NONE

Unknown acute toxicity: 0% of the mixture consists of ingredients(s) of unknown toxicity

#### III. Composition

Chemical Name	Weight-%	C.A.S. number	Trade Secret
Isobornyl Acrylate	10 - 30	5888-33-5	*
2-Hydroxyethyl Methacrylate	10 - 30	868-77-9	*
Acrylic Acid	1-5	79-10-7	*
Photoinitator	1-5	Proprietary	*
Silane Coupling Agent	1-5	Proprietary	*

<sup>\*</sup> The exact percentage (concentration) of composition has been withheld as a trade secret.

#### IV. First Aid Measures

Eve Irritation: Immediately flush eyes with plenty of water for at least 15 minutes. In case of skin contact, wash thoroughly with soap and water. Skin Contact:

Inhalation: Remove affected person to fresh air. Ingestion: Low toxicity; Seek medical attention.

If any symptoms persist seek medical attention. Note to physicians: Treat symptomatically

## V. <u>Fire-Fighting Measures</u>

Suitable extinguishing media: Use CO2, dry chemical, or foam.

Do not use a solid water stream as it may scatter and spread fire

Unsuitable extinguishing media: Specific hazards arising from the chemical: Carbon dioxide CO2), carbon monoxide (CO), oxides of nitrogen (NOX), dense black smoke.

Hazardous combustion products: Hazardous decomposition products due to incomplete combustion

Protective equipment and precautions for fire fighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

VI. Accidental Release Measure

Personal safety:

Ensue adequate ventilation. Wear Suitable gloves and eye/face protection.

Do not allow material to contaminate ground water system. Try to prevent the material from entering drains or water courses. See Section 12 for additional Ecological Information. Local authorities should be advised if significant spillages cannot be contained. Environmental safety:

Soak up with inert absorbent material (e.g. sand, silica get, acid binder, universal binder, sawdust.

Methods for cleaning up: VII. Storage and Handling Procedures.

Storage: Keep container tightly closed in a dry and well-ventilated place.

Handle in accordance with good industrial hygiene and safety practices. Ensure adequate ventilation. Protect from light. Amines, Strong oxidizing agents, Strong acids, Strong bases, Oxygen scavengers, Thiosulfates.

Incompatible products:

### VIII. Exposure Controls and Personal Protection

Chemical name	ACGIH TLV	OSHA	NIOSH IDLH
Acrylic Acid	TWA: 2PPM S*	(vacated) TWA: 10ppm	TWA: 2 ppm
		(vacated) TWA: 30 mg/m₃ S*	TWA: 6 mg/m₃

Respiratory: Positive fresh air exhaust should be provided in the work area; respiratory equipment is unnecessary in normal use. Skin

Avoid skin contact. Wear gloves and impervious protective clothing if frequent direct contact is likely. Do not wear contact lenses. Chemical safety goggles are recommended. Eyes:

IX. Physical and Chemical Properties.

Appearance: Transparent Density: Not Determined Ignition temperature: 214°F (101°C) Melting point/freezing point Not Determined Odor: Characteristic Evaporation Rate Not Determined Specific Gravity Water Solubility Values Not Determined Auto Ignition Not Determined Not Determined Oxidizing properties Explosive properties

X. Stability and reactivity

Stability: Stable under normal conditions.

Hazardous Decomposition Products:

Incompatibility: Amines, Strong oxidizing agents, Strong acids, Strong bases, Oxygen scavengers. Protect from light and heat.

8/4/2016

Page 1 of 2

XI. <u>Toxicological Information</u>

No Acute toxicity information is available for this product. Page 2 of 2

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Isobornyl Acrylate	= 4890 mg/kg (Rat)	> 5 g/kg (Rabbit)	
2-Hydroxyethyl Methacrylate	= 5050 mg/kg (Rat)	> 3000 mg/kg (Rabbit)	
Acrylic Acid	= 33500 μg/kg (Rat	= 280 μL/kg (Rabbit)	= 5300 mg/m <sub>3</sub> (Rat) 2 h
Silane Coupling Agent	= 22600 μL/kg (Rat)	= 3970 μL/kg (Rabbit)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure.

Sensitization: May cause sensitization of susceptible persons.

Mutagenic effects: No information available Reproductive toxicity: No information available.

Carcinogenicity: Contains no ingredients above reportable quantities listed as a carcinogen.

#### Numerical measures of toxicity - Product information

0% of the mixture consists of ingredients(s) of unknown toxicity Unknown acute toxicity

The following values are calculated by d on chanter 3.1 of the GHS docu

The following values are calculated based on chapter 3.1 or the Orio document				
ATEmix (oral)	ATEmix (dermal)	ATEmix (inhalation-dust/mist)		
5019 mg/kg	5511 mg/kg	15.1 mg/l		

#### XII. Ecological Information

Ecotoxicity: Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants.

2.46363% of the mixture consists of components(s) of unknown hazards to the aquatic environment.

Acute aquatic toxicity

Chemical name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish
Isobornyl Acrylate	ErC 50 = 2.7 mg/L 96 h (Pseudokirchneriella subcapitata)	EC 50 = 1.1 mg/L 48 h (Daphnia magna)	LC 50 = 1.8 mg/L 96 h (Danio rerio)
2-Hydroxyethyl Methacrylate		EC50 > 380 mg/L 48h (Daphnia Magna)	LC50 = 227 mg/L 96 h Pimephales promelas)
Acrylic Acid	EC50 0.17 mg/L 96 h (Pseudokirchneriella subcapitata) EC50 0.04 mg/L 72 h ( Desmodesmus subspicatus)	EC50 = 95mg/L 48h	LC50 = 222 mg/L 96 h (Brachydanio rerio)
Photoinitator	EC50 14.4 mg/L 72 h (Green algae)	EC50 53.9 mg/L 48 h (Daphnia magna)	

No information Bioaccumulation Chemical name log Pow

2-Hydroxyethyl Methacrylate Isobornyl Acrylate

#### XIII. <u>Disposal considerations</u>

Persistence and degradability

Waste Disposal Methods: This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). Consult the appropriate state, regional, or local regulations for additional requirements.

No information

Contaminated packaging: Dispose of in accordance with local regulation

This product contains one or more substances that are listed with the State of California as a hazardous waste.

#### XIV. Transportation information

DOT, ICAO/IATA, IMDG/IMO, TDG, MEX: Not Regulated

# XV. Regulatory Information.

TSCA Complies AICS Not listed ENCS NZIoC PICCS DSL/NDSL EINECS/ELINCS Complies Complies Not listed Not listed Complies Complies IECSC Not listed

### **US Federal Regulations**

OSHA Regulatory Status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

SARA 313: Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical name Sara 313 - Threshold Values % Acrylic Acid - 79 10-7

### Sara 311/312 Hazard Categories:

Acute health hazard Yes Chronic Health Hazard No No Fire hazard Sudden release of pressure hazard No Reactive Hazard

Cercla: This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	CERCLA/Sara RQ	Hazardous Substances RQ's	Reportable Quantity (RQ)
Acrylic acid		5000 lb.	RQ 5000 lb. final RQ
79-10-7			RQ 2270 kg final RQ

#### **US State Regulations**

# California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acrylic acid	Х	X	X
Methyl alcohol	X	X	X

## XVI. Other information

Issue Date: 2015-02-13

Revision Date: 2016/07/01

the best of our knowledge, the information contained herein is accurate. However, Deta Kits line cose not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any attential is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.